LOBITO
BULTACO

FAMOUS BULTACO

There is much more to these machines than their just being «Cute little things».

In spite of all efforts to look like a street bike, the Lobitos MK4 are simply trail, woods, and enduro bikes, evidenced by their knobby front and rear tires, small light brakes and the ability to lug a large body up and down the trails.

Enjoyment is the key word to trail riding, whether it be serious competition enduro, or just rounding-up-the-cows.

The fine handling, the high torque and the 5 speed gearbox are some of the features that help achieve this enjoyment, and at times when you may become entrapped in a difficult situation you will get the feeling that the machine is thinking for you.

HANDLING

LOBITO

SPECIFICATIONS

Lobito Mk4 125	SPECIFICATIONS	Lobito Mk4 175
MK4 125 cc.	**ENGINE**	**MK4 175 cc.**
1	Number of cylinders	1
2 stroke	Cycle	2 stroke
51.5 x 60 mm.	Bore and stroke	60.5 x 60 mm.
124.98 cc.	Displacement	174.77 cc.
14:1	Compression ratio	12:1
18.4 at 8500 rpm.	Brake horsepower	22 at 8000 rpm.
	Alloy cylinder head and alloy cylinder with hardened liner	
AMAL 625	**CARBURETOR**	AMAL 930
Electronic System with battery	**IGNITION**	Electronic System with battery
5 speeds	**GEARBOX**	5 speeds
I. 0.287:1 - II. 0.442:1 - III. 0.625:1 - IV. 0.821:1 - V. 1:1	Ratios	I. 0.287:1 - II. 0.442:1 - III. 0.625:1 - IV. 0.821:1 - V. 1:1
Multiple plates in oil bath	**CLUTCH**	Multiple plates in oil bath
	TRANSMISSION	
3/8" Chain (ASA 2035)	Primary drive	3/8" Chain (ASA 2035)
1/2" Chain (ISO-42) with tensioner	Rear drive	1/2" Chain (ISO-42) with tensioner
	SUSPENSION	
Telescopic with hydraulic dampening 6 1/2" travel (165 mm.)	Front suspension	Telescopic with hydraulic dampening 6 1/2" travel (165 mm.)
Swinging arm with hydraulic dampening 3 3/4" travel (94 mm.)	Rear suspension	Swinging arm with hydraulic dampening 3 3/4" travel (94 mm.)
	WHEELS	
2.50 x 21" Knobby tyre	Front wheel	2.50 x 21" Knobby tyre
3.50 x 18" Knobby tyre	Rear wheel	3.50 x 18" Knobby tyre
	BRAKES	
140 x 35 mm. (9600 mm²)	Front brake diameter & width	140 x 35 mm. (9600 mm²)
140 x 40 mm. (11360 mm²)	Rear brake diameter & width	140 x 40 mm. (11360 mm²)
	GENERAL	
73 mph. (118 Kms/h.)	Cruising speed	75 mph. (120 Kms/h.)
1.98 U.S. gallons (7.5 lts.)	Gas-tank capacity	1.98 U.S. gallons (7.5 lts.)
51.02"	Wheelbase	51.02"
75.83"	Overall length	75.83"
41.62" x 32.48"	Handlebars, weight and width	41.62" x 32.48"
31.89"	Saddle height	31.89"
12.5"	Ground clearance	12.5"
13.81"	Foot-rest height	13.81"
227 lbs. (103 kgs.)	Empty weight	231 lbs. (105 kgs.)

BULTACO CEMOTO

Art.° 74.34-002-1/1 Constant improvement will subject specifications to change without notice

COMPAÑIA ESPAÑOLA DE MOTORES, S. A. - San Adrián de Besós - Barcelona - SPAIN